

ECO-KC1WV-1370

Item	Value or Conclusions	
PVCfilm	Composition	Glossy finish, White & Black PVC film
	Thickness	160micron (0.16mm)
	Weight	110g/m ²
	Hole Size	1.60(mm)
	Hole Space	2.40(mm)
	Shrinking rate	< 1%
	Gloss	50
	Transparency rate	52%
	Durability	1year (in normal situations, such as without pollution and direct sunshine irradiation)
Adhesive	Adhesive Type	Half-removable, clear acrylic adhesive
	UV resistance	Good
	Applicable Temperature Range	-15°C~50°C
	Initial viscosity	Test while adhering to stainless steel, 330N/m.
	Final viscosity	Test while adhering to stainless steel, 490N/m.
Release Paper	Type	paper with one-side silicone backing
	Color	White
	Weight	175g/ m ²
Storage Period	1year (Storage temperature of 22°C, relative humidity of 50~55%)	
Durability	1year (vertically hung)	
Applications	by screenprinting or wide-format digital printing,it is applied to vehicle graphics,building murals,shopping mall, window advertising,etc.	
Attentions	Data above are updated results or conclusions of test, allowing ±5%error. Our company is responsible for nothing but that the product is in accordance with above technical data and capability. We may make amendment to the relative data or conclusions without any notice	
Quality Guarantee	Our products are manufactured with high-quality raw materials and advanced technology & equipment, guaranteed by serious & scientific quality control system. Should our products sold have any proved quality problem, we would accept unconditioned refund or change of goods. Compensation scope will be limited within certain products price. No salespeople or agents have the rights to provide guarantee or assurance beyond announcements above or any similar contracts	