

## ECO-KC500G-1370

Item	Value or Conclusions	
PVC film	Composition	Glossy Finish, white PVC film
	Thickness	100micron (0.10mm)
	Weight	140g/m2
	Shrinking rate	< 0.9%
	gloss	50
	Opaque rate	99%
	Durability	1year (in normal situations such as without pollution or direct sunshine irradiation)
Adhesive	Adhesive Type	permanent acrylic black glue
	viscosity	Good
	UV resistance	Good
	Applicable Temperature Range	- 15°C~50°C
	Initial viscosity	Test while adhering to stainless steel,550N/m.
	Final viscosity	Test while adhering to stainless steel,700N/m.
Release Paper	Type	paper with one-side silicone backing
	Color	White
	Weight	140g/m2
Storage Period	1year (Storage temperature of 22°C, relative humidity of 50~55%)	
Durability	1year (vertically hung)	
Applications	It is suitable for outdoor and indoor screenprinting and wide-format digital printing,applied to vehicle graphics,unregular surface,outdoor signs and label,etc.	
Attentions	Data above are updated results or conclusions of test, allowing $\pm 5\%$ error. Our company is responsible for nothing but that the product is in accordance with above technical data and capability. We may make amendment to the relative data or conclusions without any notice.	
Quality Guarantee	Our products are manufactured with high-quality raw materials and advanced technology & equipment, guaranteed by serious & scientific quality control system. Should our products sold have any proved quality problem, we would accept unconditioned refund or change of goods. Compensation scope will be limited within certain product's price. No salespeople or agents have the rights to provide guarantee or assurance beyond announcements above or any similar contracts.	